

150mm THICK CONCRETE FLOOR SLAB

DPC TO ARCHITECT'S APPROVAL

BRC MESH FABRIC NO. A142

1000 GAUGE POLYTHENE SHEETING 50MM THICK MURRAM/SAND RAMMED AND WELL COMPACTED BLIN 2Y8 + R6 CLIPS - 200mm CC 300mm THICK WELL COMPACTED HARDCORE (COMPACT IN LAYERS OF 150mm)

BACKFILL TO SUIT SITE CONDITIONS

200mm (NOMINAL) LOAD BEARING MASONRY STONE WALLS (CEMENT MORTAR 1:3)

3Y10-06-242 CC B2

Y8-05-200mm CC B1

50mm THICK LEAN CONCRETE BLINDING (1:4:8 MIX)

150mm THICK CONCRETE FLOOR SLAB

DPC TO ARCHITECT'S APPROVAL

BRC MESH FABRIC NO. A142

1000 GAUGE POLYTHENE SHEETING

50MM THICK MURRAM/SAND RAMMED AND WELL COMPACTED BLIN 2Y8 + R6 CLIPS - 200mm CC

300mm THICK WELL COMPACTED HARDCORE (COMPACT IN LAYERS OF 150mm)

BACKFILL TO SUIT SITE CONDITIONS

3Y10-06-242 CC B2

FOUNDATION LAYOUT - BLOCK A

3	
bivid	
avid	

<u>SHEET N^o</u>